



## Solid Press On Tire LM-302 TRT-2

### Features:

The wide tread base operates stability and lowers rolling resistance.

Super lug tread designs for good ground grasping performance and anti-wear resistance.

Suitable for tow trucks, airports, port and other machinery working.



**Tyre Size:** 8 1/2\*4\*4, 9\*5\*5, 10\*4 3/4X6 1/2, 10\*4\*6 1/4, 10\*4\*6 1/2, 10\*5\*6 1/2, 10\*5\*6 1/4, 10\*6\*6 1/2, 10\*6\*6 1/4, 10\*7\*6 1/4, 10 1/2\*5\*5, 10 1/2\*5\*6 1/2, 10 1/2\*6\*5,

Tyre Sizes				
8 1/2*4*4	12*6 1/2*8	15 1/2*6*10	18*8*14	22*10*6
9*5*5	13*3 1/2*8	16*4 1/2*10 1/2	18*9*12 1/8	22*12*16
10*4 3/4X6 1/2	13*4 1/2*8	16*5*10 1/2	18*9*14	22*14*16
10*4*6 1/4	13*5 1/2*8	16*6*10 1/2	20*5*16	22*16*16
10*4*6 1/2	13 1/2*5 1/2*8	16*7*10 1/2	20*7*16	28*12*22
10*5*6 1/2	13 1/2*4 1/2*8	16 1/4*4*11 1/4	20*8*16	22*12*22
10*5*6 1/4	13 1/2*6 1/2*8	16 1/4*5*11 1/4	20*9*16	26 10 18
10*6*6 1/2	13 1/2*7 1/2*8	16 1/4*6*11 1/4	21*5*15	28*10*20
10*6*6 1/4	14*4 1/2*8	16 1/4*7*11 1/4	21*6*15	28*12*22
10*7*6 1/4	14*5*10	16 1/4*8*11 1/4	21*7*15	28*14*22



## LANDMAX TYRE

Tyre Sizes				
10 1/2*5*5	14*8*10	16 1/4*9*11 1/4	21*8*15	28*16*22
10 1/2*5*6 1/2	15*4*11 1/4	17*5*12 1/8	21*9*15	28*18*22
10 1/2*6*5	15*5*11 1/4	18*5*12 1/8	22*4 1/2 *16	36*10*30
10 1/2*6*6 1/2	15*6*11 1/4	18*5*14	22*6*16	36*12*30
12*4*8	15*7*11 1/4	18*6*12 1/8	22*5*16	40*12*30
12*4 1/2*8	15*8*11 1/4	18*7*12 1/8	22*7*16	40*16*30
12*5*8	15*9*11 1/4	18*7*14	22*8*16	
12*5 1/2*8	15 1/2*5*10	18*8*12 1/8	22*9*16	