



LANDMAX TYRE

Truck Tires LMR288

LMR288 is a steer/trailer/drive axle all-position tire optimised for on-road application. The Long-lasting, non-directional tread design contributes to efficient fuel consumption and guarantees driving comfort.

Features:

- All position Tyres for on-road application.
- With good anti-skid and irregular wear resistance.
- The pattern is in low heating up and rolling resistance.

Tyre Size: 7.50R16LT, 8.25R16LT

Recommend to use (axle); All Position



Size	Ply Rating	Type	Section Width	Overall Diameter	Load Index Single/Dual	Max. Load Single/Dual (Kg)	Pressure Single/Dual (KPa)	Speed Index	Standard Rim	Tread Depth (mm)
7.50R16LT	12	TT	215	805	120/116	1400/1250	670/670	L	6.00G	11
	14				122/118	1500/1320	770/770	L		
	16				124/120	1600/1405	800/800	K		
8.25R16LT	12	TT	235	855	123/119	1550/1360	560/560	L	6.50H	12
	14				126/122	1700/1500	670/670	L		
	16				128/124	1800/1600	770/770	K		

Landmax International Co., Ltd.
Add: Rm201, Unit3, Lane681, Eshan Rd., Pudong New Area Shanghai China
Tel: 86 21 5873 5975 Fax: 86 21 5873 5913 Web: <https://landmaxcn.com>